

BEST AVAILABLE COPY

Mechanical drive means selected from the group consisting of conveyor belts, rollers and wheels;

and located downstream of said curling means in support of drawing the said ribbon across said curling means; wherein said mechanical drive wheel means includes at least one combination or pairing of said conveyor belt with at least one conveyor belt, roller and/or wheel wherein the said ribbon being disposed between the said combination or pairing; guide means intermediate said curling means and mechanical drive means controls the approach angle of said ribbon to said mechanical drive means.

35. A ribbon curling device according to claim 27 wherein the said delivery means supplies said unstressed curable ribbon is comprised of polypropylene material.

36. A ribbon curling device according to claim 35 wherein the said delivery means supplying said unstressed curable ribbon has means for delivering comprises multiple strands of at least two different colours.

37. A ribbon curling device according to claim 36 wherein the said drive means ~~may~~ have cutting blades for continuous or intermittent engagement with the ribbon.

38. A ribbon curling device comprising:

Delivery means for delivering a supply of unstressed curable ribbon; curling means located downstream of said delivery means for curling said ribbon; wherein the

BEST AVAILABLE COPY

approach and/or departure angle of said curable ribbon to the said curling means may be changed to suit the quality of said curable ribbon and/or the desired degree of curl tightness.

Mechanical drive means selected from the group consisting of conveyor belts, rollers and wheels;

and located downstream of said curling means in support of drawing the said ribbon across said curling means; wherein said mechanical drive wheel means includes at least one combination or pairing of said conveyor belt with at least one conveyor belt, roller and/or wheel wherein ~~the~~ said ribbon being disposed between the said combination or pairing; and a plurality of tracking guides for engagement with a different ribbon strand of said at least two curable ribbons.

39. A ribbon curling device according to claim 38 wherein the said delivery means supplies said unstressed curable ribbon is comprised of polypropylene material.

40. A ribbon curling device according to claim 39 wherein the said delivery means supplying said unstressed curable ribbon has means for delivering ~~comprises~~ multiple strands of at least two different colours.

41. A ribbon curling device according to claim 40 wherein the said drive means ~~may~~ have cutting blades for continuous or intermittent engagement with the ribbon.

BEST AVAILABLE COPY

Respectfully submitted,



Fredric Goldstein

Pro se Applicant as Inventor of record

Date: February 16, 2005

Fredric Goldstein
Varmdovagen 207
131 41 Nacka SWEDEN
Tel. 011 46 8 466 9444
Fax 011 46 8 466 9222
fgoldstein@grouponelimited.com